


用途

● 修整鋸齒部。（主要用於出口）

■ Use : For sharpening HAND SAW.

規格表 STANDARD TABLE



|  INCH mm | | HEAVY | | REGULAR | | SLIM | | X SLIM | | XX SLIM | | DOUBLE ENDER | |
|---|-----|-----------|-------------|-----------|-------------|-----------|-------------|-----------|-------------|-----------|-------------|--------------|-------------|
| | | △ W mm | ⚖ kg-doz | △ W mm | ⚖ kg-doz | △ W mm | ⚖ kg-doz | △ W mm | ⚖ kg-doz | △ W mm | ⚖ kg-doz | △ W mm | ⚖ kg-doz |
| 3 | 75 | 7.0 | 0.20 | 5.5 | 0.15 | 3.9 | 0.07 | — | — | — | — | — | — |
| 3 1/2 | 88 | 8.6 | 0.33 | 7.0 | 0.24 | 4.7 | 0.11 | — | — | — | — | — | — |
| 4 | 100 | 9.4 | 0.35 | 8.6 | 0.31 | 5.5 | 0.18 | 4.7 | 0.11 | 3.9 | 0.08 | — | — |
| 4 1/2 | 113 | 10.9 | 0.55 | 9.4 | 0.45 | 6.3 | 0.23 | 5.5 | 0.16 | 4.3 | 0.10 | — | — |
| 5 | 125 | 11.7 | 0.85 | 10.2 | 0.61 | 7.0 | 0.31 | 5.5 | 0.19 | 4.7 | 0.13 | — | — |
| 5 1/2 | 138 | 13.3 | 1.13 | 10.9 | 0.78 | 7.8 | 0.39 | 6.3 | 0.25 | 5.5 | 0.19 | — | — |
| 6 | 150 | 13.3 | 1.24 | 11.8 | 0.98 | 8.6 | 0.51 | 7.0 | 0.34 | 5.5 | 0.21 | 4.7 | 0.15 |
| 7 | 170 | 14.8 | 1.64 | 13.3 | 1.26 | 10.2 | 0.94 | 8.6 | 0.61 | 6.3 | 0.33 | 5.5 | 0.25 |
| 8 | 200 | 16.4 | 2.35 | 14.8 | 1.85 | 11.7 | 1.28 | 10.2 | 0.94 | 7.8 | 0.55 | 7.0 | 0.44 |
| 9 | 225 | 18.0 | 2.80 | 16.4 | 2.60 | 13.3 | 1.70 | — | — | — | — | 8.6 | 0.68 |
| 10 | 250 | 20.3 | 4.50 | 18.0 | 3.00 | 14.8 | 2.34 | — | — | — | — | 9.4 | 0.95 |