



**■用途**

● 鋸の目立て修正 (主として輸出用)

**■Use :** For sharpening HAND SAW.

規格表 STANDARD TABLE



|  |     | HEAVY     |            | REGULAR   |            | SLIM      |            | X SLIM    |            | XX SLIM   |            | DOUBLE ENDER |            |
|-------------------------------------------------------------------------------------|-----|-----------|------------|-----------|------------|-----------|------------|-----------|------------|-----------|------------|--------------|------------|
|                                                                                     |     | △<br>W mm | ⚖<br>kg-do | △<br>W mm | ⚖<br>kg-do | △<br>W mm | ⚖<br>kg-do | △<br>W mm | ⚖<br>kg-do | △<br>W mm | ⚖<br>kg-do | △<br>W mm    | ⚖<br>kg-do |
| INCH                                                                                | mm  |           |            |           |            |           |            |           |            |           |            |              |            |
| 3                                                                                   | 75  | 7.0       | 0.20       | 5.5       | 0.15       | 3.9       | 0.07       | —         | —          | —         | —          | —            | —          |
| 3 1/2                                                                               | 88  | 8.6       | 0.33       | 7.0       | 0.24       | 4.7       | 0.11       | —         | —          | —         | —          | —            | —          |
| 4                                                                                   | 100 | 9.4       | 0.35       | 8.6       | 0.31       | 5.5       | 0.18       | 4.7       | 0.11       | 3.9       | 0.08       | —            | —          |
| 4 1/2                                                                               | 113 | 10.9      | 0.55       | 9.4       | 0.45       | 6.3       | 0.23       | 5.5       | 0.16       | 4.3       | 0.10       | —            | —          |
| 5                                                                                   | 125 | 11.7      | 0.85       | 10.2      | 0.61       | 7.0       | 0.31       | 5.5       | 0.19       | 4.7       | 0.13       | —            | —          |
| 5 1/2                                                                               | 138 | 13.3      | 1.13       | 10.9      | 0.78       | 7.8       | 0.39       | 6.3       | 0.25       | 5.5       | 0.19       | —            | —          |
| 6                                                                                   | 150 | 13.3      | 1.24       | 11.8      | 0.98       | 8.6       | 0.51       | 7.0       | 0.34       | 5.5       | 0.21       | 4.7          | 0.15       |
| 7                                                                                   | 170 | 14.8      | 1.64       | 13.3      | 1.26       | 10.2      | 0.94       | 8.6       | 0.61       | 6.3       | 0.33       | 5.5          | 0.25       |
| 8                                                                                   | 200 | 16.4      | 2.35       | 14.8      | 1.85       | 11.7      | 1.28       | 10.2      | 0.94       | 7.8       | 0.55       | 7.0          | 0.44       |
| 9                                                                                   | 225 | 18.0      | 2.80       | 16.4      | 2.60       | 13.3      | 1.70       | —         | —          | —         | —          | 8.6          | 0.68       |
| 10                                                                                  | 250 | 20.3      | 4.50       | 18.0      | 3.00       | 14.8      | 2.34       | —         | —          | —         | —          | 9.4          | 0.95       |