



■用Ni电极沉积法固定金刚石颗粒。粘合度，研削度和耐磨性能得到提高。

■用途

●使用于陶瓷，超硬金属，锻件等高硬度材料。

■使用注意

- 轻轻接触被切削件便能够充分研削。
- 湿式研削也有效，请加入少量油后使用。

■Use : Please use it after dropping a little of oil on the working point.

Diamond Grids are fixed by Ni-plating process.

Especially it's very available for the very high hardened materials modify, i.e. Ceramics, Hard-Metals, hardened steel etc..

S類型 (金剛石粒度#200)

S-TYPE (DIAMOND GRID NO.#200)

411

規格表 STANDARD TABLE



"Precision Needle" TYPE

RED-GRIP

DIMEN-SION	TYPE	套裝 SET (每種形狀1支)	扁 HAND W × T mm	半圓 HALF ROUND W × T mm	圓 ROUND W mm	方 SQUARE W mm	三角 TRIANGULAR W mm
200L 70ℓ φ4.0A	S-5	—	8.0 × 2.0	7.0 × 2.5	φ4.0	3.5	5.0
kg-1set		0.14	0.15	0.15	0.14	0.13	0.14
No./1set		5 (each 1)	5	5	5	5	5
ITEM No.		DSST 0520	DSHI 0520	DSHA 0520	DSMA 0520	DSKA 0520	DSSA 0520
180L 60ℓ φ3.5A	S-8	—	6.5 × 1.5	6.0 × 2.0	φ3.5	3.0	4.3
kg-1set		0.11	0.12	0.12	0.11	0.11	0.11
No./1set		5 (each 1)	5	5	5	5	5
ITEM No.		DSST 0820	DSHI 0820	DSHA 0820	DSMA 0820	DSKA 0820	DSSA 0820
170L 50ℓ φ3.0A	S-10	—	5.8 × 1.1	5.5 × 1.5	φ3.0	2.7	3.8
kg-1set		0.09	0.10	0.09	0.09	0.09	0.09
No./1set		5 (each 1)	5	5	5	5	5
ITEM No.		DSST 1020	DSHI 1020	DSHA 1020	DSMA 1020	DSKA 1020	DSSA 1020
170L 40ℓ φ2.5A	S-12	—	5.0 × 1.0	4.6 × 1.4	φ2.5	2.2	3.0
kg-1set		0.08	0.08	0.08	0.08	0.08	0.08
No./1set		5 (each 1)	5	5	5	5	5
ITEM No.		DSST 1220	DSHI 1220	DSHA 1220	DSMA 1220	DSKA 1220	DSSA 1220

● #200以為都可以對應加工。

S-10 平
S-12 平

■ #400 DSHI 1040
■ #400 DSHI 1240

■ #600 DSHI 1060
■ #600 DSHI 1260